




SG-JS Cement Retarder

 Appearance:
Powder

SG-JS is a kind of retarder additives widely used in the cementitious mortars industry with small dosage but high performance.

Benefits

- Improved workability
- Good adaptability
- High set-retardation
- No reduction in final strength

Dosage

SG-JS is added to the material at the beginning of batching cycle. Mix and stir evenly.

The recommended dosage is 0.1 - 3.0 % according to the blending materials weight.

Make experiments to get the optimized result.

Or contact the technical support at info@yschempro.com.

Specifications

Appearance	Powder
Color	White
Active Content	≥ 96.5 %
Drying Loss	Max.0.5 %
pH Value	5.0 - 7.0 (20 °C, 10 % solution)

Packaging

SG-JS cement retarder is available in 25kg bags.

Applications

- Self-leveling underlayment (SLU) and self-leveling screeds
- Cementitious floor screeds
- Non-shrink and anchor grouts
- Pumpable self-leveling mortars

Storage and Shelf Life

Protect from direct sunlight, moisture and frost. Store in dry warehouse conditions between 5 to 40 °C.

Shelf life in storage conditions is 12 months.

Represented information is based on our current experience. In case of various factors affecting the result, information does not mean legal responsibility. For additional information, please contact us.



CONTACT US

Send email to info@yschempro.com
or Scan QR Code for more products
Web: www.yschempro.com