




SG-RD Gypsum Retarder

 Appearance:
Powder

SG-RD is a highly efficient set retarder in powder form for calcium sulphate (gypsum) based binder systems.

Benefits

- Improved workability
- Good adaptability
- High set-retardation
- No reduction in final strength

Dosage

SG-RD is added to the material at the beginning of batching cycle. Mix and stir evenly.

The recommended dosage is 0.03 - 0.2 % according to the blending materials weight.

Make experiments to get the optimized result.

Or contact the technical support at info@yschempro.com.

Specifications

Appearance	Powder
Color	White or brown
Bulk Density	0.4 - 0.6 g/cm ³
pH	7.0 - 9.0 (20 °C, 1% solution)
Drying Loss	≤ 3.0 %

Packaging

SG-RD gypsum retarder is available in 25kg bags.

Applications


- Gypsum plastering mortar
- Gypsum based self-leveling underlayment
- Bonding gypsum
- Caulking gypsum
- Plastering
- Putty

Storage and Shelf Life

Protect from direct sunlight, moisture and frost. Store in dry warehouse conditions between 5 to 40 °C.

Shelf life in storage conditions is 12 months.

Represented information is based on our current experience. In case of various factors affecting the result, information does not mean legal responsibility. For additional information, please contact us.



CONTACT US

Send email to info@yschempro.com
or Scan QR Code for more products
Web: www.yschempro.com