




## SG-XP Defoamer Powder

 Appearance:  
Powder

SG-XP Defoamer powder is specially designed for dry-mix mortar, to eliminate and inhibit potential foams and bubbles occurred during construction.

### Benefits

- Improved workability
- Fast defoaming
- Excellent foam inhibition
- Good adaptability in cement and gypsum

### Dosage

SG-XP defoamer powder is added to the material at the beginning of batching cycle. Mix and stir evenly.

Depending on the application, the dosage varies from 0.03 % to 0.1 % of the blending materials weight.

Make experiments to get the optimized result.

Or contact the technical support at [info@yschempro.com](mailto:info@yschempro.com).

### Specifications

Appearance	Powder
Color	White
Bulk Density	0.4 - 0.6 g/cm <sup>3</sup>
pH	6.0 - 8.0 (20 °C, 1 % solution)
Drying Loss	≤ 3.0%
Solubility	Water solvable

### Packaging

SG-XP defoamer powder is available in 25kg bags.

### Applications

- Self-leveling underlayment (SLU) and self-leveling screeds
- Calcium sulphate and cement based screeds
- Non-shrink and anchor grouts
- Repair and injection mortars
- Tile adhesives and joint fillers
- Pumpable self-leveling mortars

### Storage and Shelf Life

Protect from direct sunlight, moisture and frost. Store in dry warehouse conditions between 5 to 40 °C.

Shelf life in storage conditions is 12 months.

Represented information is based on our current experience. In case of various factors affecting the result, information does not mean legal responsibility. For additional information, please contact us.



### CONTACT US

Send email to [info@yschempro.com](mailto:info@yschempro.com)  
or Scan QR Code for more products  
Web: [www.yschempro.com](http://www.yschempro.com)